



PROFILE 300WW



POWERFUL OUTPUT

SMOOTH DIMMING

QUALITY GLASS LENSES

DURABLE METAL BODY

- 300W Warm White COB LED
- 5 Lens Options
- 6 Selectable Dimmer Curves
- Custom Dimmer Curve & Frequency

The PROFILE 300WW is our version of the well-known framing profile widely in use. Powered by a 300W warm white LED source, the PROFILE 300WW is bright and capable. Power in & out allows many lights to link on a single circuit. High quality is a feature with durable aluminum construction, and precision glass lens elements. Install or rental ready.

TECHNICAL SPECIFICATIONS

Control and Programming

DMX Channel: 1/2/3 Channel
Modes: DMX, Auto, Manual, RDM

Typical Power and Current

Peak Power Consumption: 320VA
Power Voltage: AC 100-240V, 50/60Hz
Maximum Power Linking: 6 Units on 20A

Light Source

1 x 300W warm white COB LED
Color Temperature: 3200°K
CRI ≥90

Optics

Standard Lens Angles: 19°, 26°, 36°
Optional Lens Angles: 10° & 50°

Warranty

2 year warranty on parts
and labour

Construction

Available Colors: Black
Body Material: Aluminum
Graphic LED Display for control
IP Rating: IP20

Connections

Data In/Out: 3-pin XLR M/F
Power In/Out: Powercon Seetronic

Accessories

Edison to Seetronic powerCON Cable
Mounting Bracket

Physical

Depth: 700mm
width: 270mm
Height: 263mm
weight: 9.2 kg (20.25 lbs)

Designed and Engineered in

