

- DIGITAL SIGNAGE
- COMMERCIAL
- ADVERTISING
- BILLBOARD



- FINE PITCH FOR OUTDOOR INSTALL
- THIN LIGHTWEIGHT DESIGN
- IP66 & IP65 ENVIRO RATED
- FRONT OR REAR SERVICE
- BLACK OR NATURAL ALUMINUM FRAME

	FE+ 10	FE+ 8	FE+ 6	FE+ 5	FE+ 4
Pixel Pitch	10.4 mm	7.8 mm	6.3 mm	4.8 mm	3.9 mm
Cabinet Resolution (px)	96 x 96	128 x 128	160 x 160	208 x 208	256 x 256
Module Resolution (px)	48 x 24	64 x 32	80 x 40	104 x 52	128 x 64
Brightness (nits)	≥6500	≥6500	≥6000	≥5500	≥5000
Pixel Density (dot./m²)	9,216	16,384	25,600	43,264	65,536
LED Type	SMD 2727			SMD 1921	
Module Size	500 x 250mm				
Cabinet Size (HxWxD)	1000 x 1000 x 90.5 mm				
Cabinet Material	Aluminum				
Weight of Cabinet	22 kg/m≥				
Maintenance	Front or Rear				
Viewing Angle (H/V)	140° / 120°				
Operating Temperature	-20°C to +55°C				
IP Rating	IP66 Front / IP65 Rear				
Power Input	110 / 220 Vac, 50/60 Hz [+/- 10%]				
Max Consumption	800 W/m²				
Avg Consumption	220 W/m²				
Gray Scale	14-bit or 16-bit				
Frame Refresh	50 / 60 Hz				
Data Refresh	≥1920 Hz -or- ≥3840 Hz				
LED Lifetime	≥ 100,000 hours				
Certifications	CE, FCC, CSA SPE1000				

